



Mobile High Pressure Cleaner, electrically-heated FHE 718 TCC

► Data Sheet

MADE IN GERMANY

1.0	Type	FHE 718 TCC	
2.0	Capacity		
2.1	Mains connection	400 V 3 AC 50 Hz	
2.2	Nominal consumption	23 kW 31 A	
2.3	Heat capacity	18 kW	
2.4	Tank content	27 l	
2.5	Warm-up time	6 minutes	
2.6	at a water inlet temperature of 15°C		
2.6	Connecting cable 4 x 1.5 mm ²	5 m with mains plug	
3.0	High pressure stage		
3.1	Working pressure	180 bar	
3.2	Flow rate	700 l/h	
3.3	Operating temperature	40 °C	
	at a water inlet temperature of 15°C		
4.0	Low pressure stage		
4.1	Working pressure	60 bar	
4.2	Flow rate	400 l/h	
4.3	Operating temperature	55 °C	
	at a water inlet temperature of 15 °C		
5.0	Specification		
5.1	High pressure pump with 3 solid ceramic plungers	Type NP 10/11	Order nr. 7041056000
5.2	Overflow safety valve	Type UL 250 HF	Order nr. 2073890000
5.3	Spray lance with plug nipple		Order nr. 1508023
5.4	Spray gun TCC with plug-in coupling		Order nr. 1508026
5.5	High pressure flat jet nozzle	Type 25035	Order nr. 7040692000
5.6	10 m high pressure hose		Order nr. 2051560000
5.7	Electrical motor 4 kW		Order nr. 7041524000
5.8	with high pressure flat jet nozzle	Type 2505	Order nr. 7023230000
5.9	with 10 m high pressure hose	Type DN 8	Order nr. 2051560000
5.10	Electrical motor for high pressure pump drive	Performance 4 kW	Order nr. 7041524000
5.11	Connecting cable 5 x 4 mm ²	5 m with mains plug	
		32 A	
6.0	Dimensions with trolley (LxWxH)	1245 x 590 x 845 mm	
7.0	Weight	120 kg	

