



# Mobile High pressure cleaner, unheated FC 918 M

## ► Data Sheet

MADE IN GERMANY

<b>1.0</b>	<b>Type</b>	FC 918 M	
<b>2.0</b>	<b>Capacity</b>		
2.1	Mains connection	400 V 3 AC 50 Hz	
2.2	Nominal consumption	5,3 kW 9,5 A	
2.3	Working pressure	180 bar	
2.4	Water - volume flow	14,5 l/min	
2.5	Operating temperature maximum	70 °C	
<b>3.0</b>	<b>Specification</b>		
3.1	High pressure pump with 3 solid ceramic plungers	Type NP 16/13	Order nr. 7041307000
3.2	Unloader safety valve	Type VS - ULH 180	Order nr. 2098857000
3.3	protects the high pressure system		
3.4	with injector 2,2 for the dosage of cleaning and preserving agents		
3.5	Duplex-spray lance for pressure regulation		Order nr. 2098290000
3.6	with low pressure stage for the dosage of cleaning and preserving agents		
3.7	with rotating screw union		Order nr. 2085600000
3.8	with mechanical spray gun		Order nr. 7041097000
3.9	with high pressure flat jet nozzle	Type 25045	Order nr. 7027160000
3.10	with low pressure flat jet nozzle	Type 4040	Order nr. 7025330000
3.11	with high pressure hose 10 m	Type DN 8	Order nr. 2051560000
3.12	Electrical motor for high pressure pump drive	Capacity 4 kW	Order nr. 7040633000
3.13	M - Control with bypass operation		
3.14	Connecting cable 4 x 1,5 mm <sup>2</sup>	6 m with mains plug	
<b>4.0</b>	<b>Dimensions with trolley (LxWxH)</b>	16A 856x545x918 mm	
<b>5.0</b>	<b>Weight</b>	76 kg	

